

PRODUCT DATA SHEET

2026-09-21



Article number:

5A20685322SS


Braked castor 200 mm, total stop brake, rubber-tyr

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with black rubber-tyre. Hub made of PP. Roller bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	200 mm
Totalt height	240 mm
Load Capacity (dynamic)	205 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Rubber
Bearing	Roller bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	85° Shore A
Brake	Total brake
Width of tread	48 mm
Hub Hole Diameter	12 mm
Material Hub	Polypropylen (pp)
Top Hole	11 mm
Fork Width	61 mm
Dyn. Load Capacity (4km/)	205 kg
Color Tread	Black
Offset	54 mm
Material Thickness Bracket	3 mm
Materialthickplate	4 mm
Swivel radius	162 mm
Product Weight	3.17 kg
Temperature Range	-20°C to +60°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.