

PRODUCT DATA SHEET

2026-09-21



Article number:

6J10685932SZ-FE-M

Braked castor 100 mm, total stop brake, elastic ru

Swivel bracket. Welded, zinc plated castor fitted with a total stop brake and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel with black elastic rubber-tyre. Hub made of cast iron. Double Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	100 mm
Totalt height	145 mm
Load Capacity (dynamic)	210 kg
Fitting	Top plate
Material Tread	Elastic Rubber
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	75° Shore A
Brake	Total brake
Width of tread	50 mm
Material Hub	Cast Iron
Top Hole	11 mm
Dyn. Load Capacity (4km/)	210 kg
Color Tread	Black
Offset	46 mm
Material Thickness Bracket	6 mm
Materialthickplate	8 mm
Temperature Range	-20°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.