

Article number:

6J12685232V-G

Braked castor 125 mm, total stop brake, PA6G-wheel

Swivel bracket. Welded, zinc plated castor fitted with a total stop brake and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel made of white Nylon/PA6G. Doubla Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	125 mm
Totalt height	170 mm
Load Capacity (dynamic)	1400 kg
Fitting	Top plate
Material Tread	Nylon PA6G (Cast)
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	85° Shore D
Brake	Total brake
Width of tread	55 mm
Material Hub	Nylon PA6G (Cast)
Top Hole	11 mm
Dyn. Load Capacity (4km/)	1400 kg
Color Tread	White
Offset	57 mm
Material Thickness Bracket	6 mm
Materialthickplate	8 mm
Temperature Range	-20°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.