

Article number:

6K15680432PZ-FE-V2

Fixed castor 150 mm, elastic PU-tyre

Fixed bracket made of zinc-chromatized welded steel. Top plate fitting. Wheel axle with nut. Wheel with green elastic PU-tyre. Hub made of cast iron. Double Ball bearing.



Image may differ from the actual product.\*

SPECIFICATIONS

|                            |                     |
|----------------------------|---------------------|
| Diameter                   | 150 mm              |
| Totalt height              | 200 mm              |
| Load Capacity (dynamic)    | 450 kg              |
| Fitting                    | Top plate           |
| Material Tread             | Elastic Polyurethan |
| Bearing                    | Double Ball bearing |
| Plate Size                 | 150x110 mm          |
| CC Distance                | 105x80 mm           |
| Thread hardness (Shore°)   | 83° Shore A         |
| Width of tread             | 38 mm               |
| Material Hub               | Cast Iron           |
| Top Hole                   | 12 mm               |
| Fixed                      | Yes                 |
| Dyn. Load Capacity (4km/)  | 450 kg              |
| Color Tread                | Green               |
| Material Thickness Bracket | 6 mm                |
| Materialthickplate         | 6 mm                |
| Temperature Range          | -20°C to +70°C      |

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.