

Article number:

6N25695232V-G

Braked castor 250 mm, wheel brake, PA6G-wheel

Swivel bracket. Welded, zinc plated castor fitted with a wheel brake and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel made of white Nylon/PA6G. Doubla Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	250 mm
Totalt height	314 mm
Load Capacity (dynamic)	5000 kg
Fitting	Top plate
Material Tread	Nylon PA6G (Cast)
Bearing	Double Ball bearing
Plate Size	200x160 mm
CC Distance	160x120 mm
Thread hardness (Shore°)	85° Shore D
Brake	Wheel brake
Width of tread	80 mm
Material Hub	Nylon PA6G (Cast)
Top Hole	18 mm
Dyn. Load Capacity (4km/)	5000 kg
Color Tread	White
Offset	78 mm
Material Thickness Bracket	12 mm
Materialthickplate	15 mm
Temperature Range	-20°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.