

Article number:

6Q30695432OZ-FE-M

Braked castor 300 mm, wheel brake, PU-tyre

Swivel bracket. Welded, zinc plated castor fitted with a wheel brake and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel with red PU-tyre. Hub made of cast iron. Double Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	300 mm
Totalt height	395 mm
Load Capacity (dynamic)	2800 kg
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Double Ball bearing
Plate Size	255x200 mm
CC Distance	210x160 mm
Thread hardness (Shore°)	93° Shore A
Brake	Wheel brake
Width of tread	100 mm
Material Hub	Cast Iron
Top Hole	18 mm
Dyn. Load Capacity (4km/)	2800 kg
Color Tread	Red
Offset	85 mm
Material Thickness Bracket	12,2 mm
Materialthickplate	27,5 mm
Temperature Range	-20°C to +85°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.