

Article number:

6S12696932SZ-FE-M

Braked castor twin wheel 125 mm, wheel brake, elas

Swivel bracket made for a twin wheel setup. Welded, zinc plated castor fitted with a wheel brake and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel with black elastic rubber-tyre. Hub made of cast iron. Double Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	125 mm
Totalt height	185 mm
Load Capacity (dynamic)	500 kg
Fitting	Top plate
Material Tread	Elastic Rubber
Bearing	Double Ball bearing
Plate Size	175x140 mm
CC Distance	140x105 mm
Thread hardness (Shore°)	75° Shore A
Brake	Wheel brake
Width of tread	50 mm
Material Hub	Cast Iron
Top Hole	14 mm
Dyn. Load Capacity (4km/)	500 kg
Color Tread	Black
Offset	45 mm
Material Thickness Bracket	8 mm
Materialthickplate	15 mm
Temperature Range	-20°C to +85°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.