

Article number:

6U20697232V-G

Braked castor twin wheel 200 mm, directional lock,

Swivel bracket made for a twin wheel setup. Welded, zinc plated castor fitted with a 4-way directional lock and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel made of white Nylon/PA6G. Double Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	200 mm
Totalt height	264 mm
Load Capacity (dynamic)	5000 kg
Fitting	Top plate
Material Tread	Nylon PA6G (Cast)
Bearing	Double Ball bearing
Plate Size	200x160 mm
CC Distance	160x120 mm
Thread hardness (Shore°)	85° Shore D
Brake	Directional lock
Width of tread	80 mm
Material Hub	Nylon PA6G (Cast)
Top Hole	18 mm
Dyn. Load Capacity (4km/)	5000 kg
Color Tread	White
Offset	65 mm
Material Thickness Bracket	12 mm
Materialthickplate	15 mm
Temperature Range	-20°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.