

Article number:

6U3069D432OZ-FE-M

Braked castor twin wheel 300 mm, directional lock,

Swivel bracket made for a twin wheel setup. Welded, zinc plated castor fitted with a 4-way directional lock and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel with red PU-tyre. Hub made of cast iron. Double Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	300 mm
Totalt height	375 mm
Load Capacity (dynamic)	3900 kg
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Double Ball bearing
Plate Size	200x160 mm
CC Distance	160x120 mm
Thread hardness (Shore°)	93° Shore A
Brake	Wheel brake/Directional lock
Width of tread	75 mm
Material Hub	Cast Iron
Top Hole	18 mm
Dyn. Load Capacity (4km/)	3600 kg
Color Tread	Red
Offset	80 mm
Material Thickness Bracket	12 mm
Materialthickplate	15 mm
Temperature Range	-20°C to +85°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.