

Article number:

5610666933DS

Fixed castor 100 mm, elastic rubber-tyre, wheel br

Housing made of zinc-chromatized, pressed steel with plate fixing 105x85 mm, screwed wheel axel. Wheel with precision ball bearing and blue elastic tyre, RAL 5010. Hub and washer in black PA6. Braked



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	132 mm
Load Capacity (dynamic)	225 kg
Castor model	Fix
Fitting	Top plate
Material Tread	Elastic Rubber
Bearing	Ball bearing
Plate Size	105x85 mm
CC Distance	80x60 mm
Thread hardness (Shore°)	75° Shore A
Brake	Wheel brake
Width of tread	36 mm
Hub Hole Diameter	10 mm
Material Hub	Nylon PA6
Top Hole	12,5x9 mm
Fork Width	48 mm
Fixed	Yes
Color Tread	Blue
Teststandard	EN 12532
Material Thickness Bracket	2 mm
Materialthickplate	2 mm
Product Weight	0.73 kg
Temperature Range	-30°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.