

PRODUCT DATA SHEET

2026-09-21



Article number:

5810000433ESD1

Swivel castor 100 mm, TPU-tyre, conductiv

Swivel bracket. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Center hole fitting. Wheel axle with nut. Wheel with grey TPU-tyre. Hub made of black Nylon/PA6 with threadguards. Ball bearing. ESD. Conductivity : ? 1 M?



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	132 mm
Load Capacity (dynamic)	225 kg
Castor model	Swivel
Fitting	Center hole
Material Tread	Polyurethane
Bearing	Ball bearing
CC Distance	80x60 mm
Thread hardness (Shore°)	98° Shore A
Centre Bolt Hole	12.4 mm
Width of tread	36 mm
Hub Hole Diameter	10 mm
Material Hub	Nylon PA6
ESD	Yes
Fork Width	47 mm
Color Tread	Grey
Teststandard	EN 12532
Offset	41 mm
Material Thickness Bracket	2.5 mm
Swivel radius	91 mm
Product Weight	0.79 kg
Temperature Range	-30°C to +70°C
ESD	≤ 1 MΩ

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.