

PRODUCT DATA SHEET

2026-09-21



Article number:

5810005233ESD1

Swivel castor 100 mm, PA6-wheel, conductiv, total

Swivel bracket. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Center hole fitting. Wheel axle with nut. Wheel with roller bearing, nature PA6, threadguards. Ball bearing. ESD. Total stop brake. Conductivity : ? 1 M?



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	100 mm
Totalt height	132 mm
Load Capacity (dynamic)	170 kg
Castor model	Brake
Fitting	Center hole
Material Tread	Polyamide / Nylon PA6
Bearing	Ball bearing
CC Distance	80x60 mm
Thread hardness (Shore°)	98° Shore A
Centre Bolt Hole	12.4 mm
Brake	Total brake
Width of tread	36 mm
Material Hub	Nylon PA6
ESD	Yes
Color Tread	Grey
Teststandard	EN 12532
Offset	41 mm
Material Thickness Bracket	2.5 mm
Swivel radius	129 mm
Product Weight	0.94 kg
Temperature Range	-30°C to +70°C
ESD	≤ 1 MΩ

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.