

Article number:

5810667333GG

Swivel castor 100 mm, directional lock, TPE-tyre

Swivel bracket with directional lock. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with grey TPE-tyre. Hub made of grey PP with threadguards. Ball bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	132 mm
Load Capacity (dynamic)	100 kg
Castor model	Swivel
Fitting	Top plate
Material Tread	TPE
Bearing	Ball bearing
Plate Size	105x85 mm
CC Distance	80x60 mm
Thread hardness (Shore°)	85° Shore A
Brake	Directional lock
Width of tread	32 mm
Material Hub	Polypropylen (pp)
Top Hole	12,5x9 mm
Static Load Capacity	200 kg
Color Tread	Grey
Teststandard	EN 12530
Offset	41 mm
Material Thickness Bracket	2.5 mm
Materialthickplate	3 mm
Swivel radius	129 mm
Product Weight	1 kg
Temperature Range	-20°C to +50°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.