

# PRODUCT DATA SHEET

2026-09-21



Article number:

5812005233ESD1

Swivel castor 125 mm, PA6-wheel, conductiv, total

Swivel bracket. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Center hole fitting. Wheel axle with nut. Wheel with roller bearing, nature PA6, threadguards. Ball bearing. ESD. Total stop brake. Conductivity : ? 1 M?



Image may differ from the actual product.\*

## SPECIFICATIONS

|                            |                       |
|----------------------------|-----------------------|
| Diameter                   | 125 mm                |
| Totalt height              | 157 mm                |
| Load Capacity (dynamic)    | 200 kg                |
| Castor model               | Brake                 |
| Fitting                    | Center hole           |
| Material Tread             | Polyamide / Nylon PA6 |
| Bearing                    | Ball bearing          |
| CC Distance                | 80x60 mm              |
| Thread hardness (Shore°)   | 98° Shore A           |
| Centre Bolt Hole           | 12.4 mm               |
| Brake                      | Total brake           |
| Width of tread             | 36 mm                 |
| Material Hub               | Nylon PA6             |
| ESD                        | Yes                   |
| Color Tread                | Grey                  |
| Teststandard               | EN 12532              |
| Offset                     | 42 mm                 |
| Material Thickness Bracket | 2.5 mm                |
| Swivel radius              | 129 mm                |
| Product Weight             | 0.98 kg               |
| Temperature Range          | -30°C to +70°C        |
| ESD                        | ≤ 1 MΩ                |

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.