

Article number:

**5812005313SS-44**

Braked castor 125 mm, total stop brake, TPE-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Center hole fitting for M12 screw. Wheel axle with nut. Wheel with black TPE-tyre. Hub made of black PP. Plain bearing.



Image may differ from the actual product.\*

### SPECIFICATIONS

|                            |                   |
|----------------------------|-------------------|
| Diameter                   | 125 mm            |
| Totalt height              | 157 mm            |
| Load Capacity (dynamic)    | 100 kg            |
| Fitting                    | Center hole       |
| Material Tread             | TPE               |
| Bearing                    | Plain bearing     |
| Thread hardness (Shore°)   | 85° Shore A       |
| Centre Bolt Hole           | 12.4 mm           |
| Brake                      | Total brake       |
| Width of tread             | 38 mm             |
| Material Hub               | Polypropylen (pp) |
| Dyn. Load Capacity (4km/)  | 100 kg            |
| Color Tread                | Black             |
| Offset                     | 42 mm             |
| Material Thickness Bracket | 2.5 mm            |
| Temperature Range          | -20°C to +60°C    |

*Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.*