

Article number:

5812660233ESD1

Swivel castor 125 mm, PA6-wheel, conductiv

Swivel bracket. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with roller bearing, nature PA6, threadguards. Ball bearing. Conductivity : ? 1 M?



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	125 mm
Totalt height	157 mm
Load Capacity (dynamic)	200 kg
Castor model	Swivel
Fitting	Top plate
Material Tread	Polyamide / Nylon PA6
Bearing	Ball bearing
Plate Size	105x85 mm
CC Distance	80x60 mm
Thread hardness (Shore°)	98° Shore A
Width of tread	36 mm
Material Hub	Nylon PA6
Top Hole	12,5x9 mm
ESD	Yes
Fork Width	47 mm
Color Tread	Grey
Teststandard	EN 12532
Offset	41 mm
Material Thickness Bracket	2.5 mm
Materialthickplate	3 mm
Swivel radius	104.5 mm
Product Weight	0.93 kg
Temperature Range	-30°C to +70°C
ESD	≤ 1 MΩ

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.