

Article number:

5816685433BZ-ALU


Braked castor 160 mm, total stop brake, PU-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with orange PU-tyre. Hub made of aluminium. Ball bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	160 mm
Totalt height	195 mm
Load Capacity (dynamic)	400 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	93° Shore A
Brake	Total brake
Width of tread	50 mm
Material Hub	Aluminium
Top Hole	11x14 mm
Dyn. Load Capacity (4km/)	400 kg
Color Tread	Orange
Teststandard	EN 12532
Offset	53 mm
Material Thickness Bracket	3 mm
Materialthickplate	3.5 mm
Swivel radius	167 mm
Product Weight	2.88 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.