

# PRODUCT DATA SHEET

2026-09-21



Article number:

5A08660922GS


Swivel castor 80 mm, elastic rubber-tyre

Swivel bracket. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with grey elastic rubber-tyre. Hub made of black Nylon/PA6. Rollerbearing.



Image may differ from the actual product.\*

## DIMENSIONS



## SPECIFICATIONS

|                            |                |
|----------------------------|----------------|
| Diameter                   | 80 mm          |
| Totalt height              | 108 mm         |
| Load Capacity (dynamic)    | 100 kg         |
| Castor model               | Swivel         |
| Fitting                    | Top plate      |
| Material Tread             | Elastic Rubber |
| Bearing                    | Roller bearing |
| Plate Size                 | 105x83 mm      |
| CC Distance                | 80x60 mm       |
| Thread hardness (Shore°)   | 65° Shore A    |
| Width of tread             | 34 mm          |
| Material Hub               | Nylon PA6      |
| Top Hole                   | 9 mm           |
| Dyn. Load Capacity (4km/)  | 100 kg         |
| Color Tread                | Grey           |
| Offset                     | 41 mm          |
| Material Thickness Bracket | 2.5 mm         |
| Materialthickplate         | 3 mm           |
| Product Weight             | 0.74 kg        |
| Temperature Range          | -20°C to +60°C |

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.