

PRODUCT DATA SHEET

2026-09-21



Article number:

5A10665322GS


Braked castor 100 mm, total stop brake, rubber-tyr

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with grey rubber-tyre. Hub made of black PP. Roller bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	128 mm
Load Capacity (dynamic)	70 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Rubber
Bearing	Roller bearing
Plate Size	105x85 mm
CC Distance	80x60 mm
Thread hardness (Shore°)	85° Shore A
Brake	Total brake
Width of tread	27 mm
Material Hub	Polypropylen (pp)
Top Hole	9 mm
Fork Width	46 mm
Dyn. Load Capacity (4km/)	70 kg
Color Tread	Grey
Offset	45 mm
Material Thickness Bracket	2.5 mm
Materialthickplate	2.5 mm
Swivel radius	124 mm
Product Weight	1.01 kg
Temperature Range	-20°C to +60°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.