

PRODUCT DATA SHEET

2026-09-23



Article number:

5A10665432DS


Braked castor 100 mm, total stop brake, TPU-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with blue TPU-tyre. Hub made of black Nylon/PA6 with threadguards. Ball bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	128 mm
Load Capacity (dynamic)	200 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Ball bearing
Plate Size	105x85 mm
CC Distance	80x60 mm
Thread hardness (Shore°)	98° Shore A
Brake	Total brake
Width of tread	36 mm
Material Hub	Nylon PA6
Top Hole	9 mm
Fork Width	46 mm
Dyn. Load Capacity (4km/)	200 kg
Color Tread	Blue
Offset	45 mm
Material Thickness Bracket	2,5 mm
Materialthickplate	2,5 mm
Swivel radius	124 mm
Product Weight	0,98 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.