

PRODUCT DATA SHEET

2026-09-21



Article number:

5A10665932GS


Braked castor 100 mm, grey elastic rubber-tyre, PA

Pressed, zinc plated swivel castor. Swivel head with double ball race, assembled with a kingpin. Top plate fitting. Total brake. Elastic grey rubber wheel on nylon centre.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	128 mm
Load Capacity (dynamic)	250 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Elastic Rubber
Bearing	Ball bearing
Plate Size	105x85 mm
CC Distance	80x60 mm
Thread hardness (Shore°)	75° Shore A
Brake	Total brake
Width of tread	36 mm
Material Hub	Nylon PA6
Top Hole	9 mm
Fork Width	46 mm
Dyn. Load Capacity (4km/)	250 kg
Color Tread	Grey
Offset	45 mm
Material Thickness Bracket	2.5 mm
Materialthickplate	2.5 mm
Swivel radius	124 mm
Product Weight	1.03 kg
Temperature Range	-20°C to +60°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.