

Article number:

**5A12005232N**

Braked castor 125 mm, total stop brake, PA6-wheel

Pressed, zinc plated swivel castor. Swivel head with double ball race, assembled with a kingping. Total brake. Nature nylon wheel PA6.



Image may differ from the actual product.\*

**SPECIFICATIONS**

|                            |                       |
|----------------------------|-----------------------|
| Diameter                   | 125 mm                |
| Totalt height              | 155 mm                |
| Load Capacity (dynamic)    | 200 kg                |
| Castor model               | Brake                 |
| Fitting                    | Center hole           |
| Material Tread             | Polyamide / Nylon PA6 |
| Bearing                    | Ball bearing          |
| Thread hardness (Shore°)   | 75° Shore D           |
| Centre Bolt Hole           | 13 mm                 |
| Brake                      | Total brake           |
| Width of tread             | 36 mm                 |
| Hub Hole Diameter          | 8 mm                  |
| Material Hub               | Nylon PA6             |
| Fork Width                 | 46 mm                 |
| Dyn. Load Capacity (4km/)  | 200 kg                |
| Color Tread                | Nature                |
| Offset                     | 44 mm                 |
| Material Thickness Bracket | 2.5 mm                |
| Swivel radius              | 124 mm                |
| Product Weight             | 0.9 kg                |
| Temperature Range          | -20°C to +70°C        |

*Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.*