

PRODUCT DATA SHEET

2026-09-21



Article number:

5A12005322SS

Braked castor 125 mm, total stop brake, rubber-tyr

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Center hole fitting for M12 screw. Wheel axle with nut. Wheel with black rubber-tyre. Hub made of PP. Roller bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	125 mm
Totalt height	155 mm
Load Capacity (dynamic)	100 kg
Castor model	Brake
Fitting	Center hole
Material Tread	Rubber
Bearing	Roller bearing
Thread hardness (Shore°)	85° Shore A
Centre Bolt Hole	13 mm
Brake	Total brake
Width of tread	38 mm
Hub Hole Diameter	8 mm
Material Hub	Polypropylen (pp)
Fork Width	46 mm
Dyn. Load Capacity (4km/)	100 kg
Color Tread	Black
Teststandard	EN 12532
Offset	44 mm
Material Thickness Bracket	2.5 mm
Swivel radius	124 mm
Product Weight	1.16 kg
Temperature Range	-20°C to +60°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.