

Article number:

5A12685432BV-HD


Braked castor 125 mm, total stop brake, TPU-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with red TPU-tyre. Hub made of Nylon/PA6. Double Ball bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	125 mm
Totalt height	163 mm
Load Capacity (dynamic)	400 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	98° Shore A
Brake	Total brake
Width of tread	45 mm
Hub Hole Diameter	12 mm
Material Hub	Nylon PA6
Top Hole	11 mm
Fork Width	61 mm
Dyn. Load Capacity (4km/)	400 kg
Color Tread	Red
Offset	60 mm
Material Thickness Bracket	3 mm
Materialthickplate	4 mm
Swivel radius	124 mm
Product Weight	2.25 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.