

Article number:

5A16685932PZ-ALU


Braked castor 160 mm, total stop brake, elastic PU

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with green elastic PU-tyre. Hub made of aluminum. Double Ball bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	160 mm
Totalt height	200 mm
Load Capacity (dynamic)	350 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Elastic Polyurethan
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	83° Shore A
Brake	Total brake
Width of tread	50 mm
Hub Hole Diameter	12 mm
Material Hub	Aluminium
Top Hole	11 mm
Fork Width	61 mm
Dyn. Load Capacity (4km/)	350 kg
Color Tread	Green
Offset	56 mm
Material Thickness Bracket	3 mm
Materialthickplate	4 mm
Swivel radius	159 mm
Product Weight	2.91 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.