

Article number:

5C10685432OZB-ALU


Braked castor 100 mm, total stop brake, elastic co

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with orange elastic convex PU-tyre. Hub made of aluminum. Double Ball bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	140 mm
Load Capacity (dynamic)	400 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Elastic Polyurethan
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	93° Shore A
Brake	Total brake, front
Width of tread	50 mm
Material Hub	Aluminium
Top Hole	11 mm
Dyn. Load Capacity (4km/)	400 kg
Color Tread	Brown
Offset	40 mm
Material Thickness Bracket	3.5 mm
Materialthickplate	4 mm
Product Weight	2.47 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.