

PRODUCT DATA SHEET

2026-09-21



Article number:

4005486601GS-15

Braked castor 50 mm, wheel brake, TPE-tyre

Swivel bracket with wheel brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Mounted screw M8. Riveted wheel axle. Wheel with grey TPE-tyre. Hub made of black PP. Plain bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	50 mm
Totalt height	64 mm
Load Capacity (dynamic)	40 kg
Castor model	Brake
Fitting	Mounted Screw
Material Tread	TPE
Bearing	Rivet
Thread hardness (Shore°)	85° Shore A
Threaded Stem	M8x15 m
Brake	Wheel brake
Width of tread	20 mm
Material Hub	Polypropylen (pp)
Info	With washer
Dyn. Load Capacity (4km/)	40 kg
Color Tread	Grey
Teststandard	EN 12530
Offset	17,5 mm
Material Thickness Bracket	1,5 mm
Swivel radius	65 mm
Product Weight	0,12 kg
Temperature Range	-20°C to +50°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.