

Article number:

4107655411SSS

Braked castor 75 mm, total stop brake, TPU-tyre

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Black lacquered. Riveted wheel axle. Wheel with black TPU-tyre. Hub made of black PP with threadguards. Plain bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	75 mm
Totalt height	99 mm
Load Capacity (dynamic)	55 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Plain bearing
Plate Size	60x60 mm
CC Distance	46x46 mm
Thread hardness (Shore°)	98° Shore A
Brake	Total brake
Width of tread	24 mm
Material Hub	Polypropylen (pp)
Top Hole	8,5x6,5 mm
Painted Housing	Black
Color Tread	Black
Teststandard	EN 12530
Offset	35 mm
Material Thickness Bracket	2 mm
Materialthickplate	2 mm
Swivel radius	82 mm
Product Weight	0,33 kg
Temperature Range	-20°C to +50°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.