

Article number:

4110655312GS

Braked castor 100 mm, total stop brake, TPE-tyre,

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Screwed wheel axle. Wheel with grey TPE-tyre. Hub made of black PP. Threadguards in metal. Plain bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	121 mm
Load Capacity (dynamic)	55 kg
Fitting	Top plate
Material Tread	TPE
Bearing	Plain bearing
Plate Size	60x60 mm
CC Distance	46x46 mm
Thread hardness (Shore°)	85° Shore A
Brake	Total brake
Width of tread	24 mm
Hub Width	25 mm
Hub Hole Diameter	10 mm
Material Hub	Polypropylen (pp)
Top Hole	8,5x6,5 mm
Color Tread	Grey
Teststandard	EN 12530
Offset	37 mm
Material Thickness Bracket	2 mm
Materialthickplate	2 mm
Swivel radius	95 mm
Temperature Range	-20°C to +50°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.