

Article number:

4310655632ESD1

Braked castor 100 mm, total stop brake, TPU-tyre,

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with grey TPE-tyre. Hub made of grey Nylon/PA6 with threadguards. Ball bearing. ESD.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	100 mm
Totalt height	126 mm
Load Capacity (dynamic)	70 kg
Castor model	Brake
Fitting	Top plate
Material Tread	TPE
Bearing	Ball bearing
Plate Size	60x60 mm
CC Distance	46x46 mm
Thread hardness (Shore°)	85° Shore A
Brake	Total brake
Width of tread	32 mm
Material Hub	Nylon PA6
Top Hole	8,5x6,5 mm
ESD	Yes
Color Tread	Grey
Offset	41 mm
Material Thickness Bracket	2,5 mm
Materialthickplate	2 mm
Swivel radius	112 mm
Product Weight	0,59 kg
Temperature Range	-20°C to +50°C
ESD	≤ 1 MΩ

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.