

Article number:

4407655412GS

Braked castor twin-wheel 75 mm with total stop bra

Swivel bracket for twin wheels with total brake. Sheet metal pressed, galvanized castor with ball bearings in the swivel head. Top plate fitting. Wheel axle with nut. Wheel with grey TPU-tyre. Hub made of black PP with steel threadguards. Plain bearing.



Image may differ from the actual product.\*

DIMENSIONS



SPECIFICATIONS

|                            |                   |
|----------------------------|-------------------|
| Diameter                   | 75 mm             |
| Totalt height              | 107 mm            |
| Load Capacity (dynamic)    | 90 kg             |
| Castor model               | Brake             |
| Fitting                    | Top plate         |
| Material Tread             | Polyurethane      |
| Bearing                    | Plain bearing     |
| Plate Size                 | 60x60 mm          |
| CC Distance                | 46x46 mm          |
| Thread hardness (Shore°)   | 98° Shore A       |
| Brake                      | Total brake       |
| Width of tread             | 24 mm             |
| Material Hub               | Polypropylen (pp) |
| Top Hole                   | 8,5x6,5 mm        |
| Color Tread                | Grey              |
| Offset                     | 39 mm             |
| Material Thickness Bracket | 2,5 mm            |
| Materialthickplate         | 2 mm              |
| Swivel radius              | 82 mm             |
| Product Weight             | 0,77 kg           |
| Temperature Range          | -20°C to +50°C    |

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.