

Article number:

5A20005322SR-LG

Braked castor 200 mm, total stop brake, pneumatic-

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Center hole fitting for M12 screw. Wheel axle with nut. Wheel with balck pneumatic rubber-tyre. Hub made of red PP. Roller bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	200 mm
Totalt height	240 mm
Load Capacity (dynamic)	60 kg
Castor model	Brake
Fitting	Center hole
Material Tread	Pneumatic wheel
Bearing	Roller bearing
Thread hardness (Shore°)	65° Shore A
Centre Bolt Hole	13 mm
Brake	Total brake
Width of tread	50 mm
Hub Hole Diameter	12 mm
Material Hub	Polypropylen (pp)
Pneumatic Wheel	Yes
Diameter second/outer	24 mm
Wheel Pattern	Ribbed
No. of Plies	2 st
Fork Width	61 mm
Color Tread	Red
Offset	53 mm
Material Thickness Bracket	3 mm
Swivel radius	162 mm
Product Weight	2,15 kg
Temperature Range	-20°C to +60°C

Numeric values in the technical specification may be nominal/rounded to the nearest standard dimension. To see exact values, please refer to the drawing.