

# PRODUCT DATA SHEET

2024-04-10



Article number:

5A16685212N-HDX


Braked castor 160 m, total stop brake, PA6-wheel

Swivel bracket with total stop brake. Pressed stainless steel with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel made of white Nylon/PA6. Plain bearing.



Image may differ from the actual product.\*

## DIMENSIONS



## SPECIFICATIONS

|                            |                      |
|----------------------------|----------------------|
| Diameter                   | 160 mm               |
| Totalt height              | 200 mm               |
| Load Capacity (dynamic)    | 350 kg               |
| Castor model               | Brake                |
| Fitting                    | Top plate            |
| Material Tread             | Nylon PA6            |
| Bearing                    | Plain bearing        |
| Plate Size                 | 140x110 mm           |
| CC Distance                | 105x80 mm            |
| Thread hardness (Shore°)   | 83° Shore D          |
| Brake                      | Total brake          |
| Width of tread             | 45 mm                |
| Material Hub               | Nylon PA6            |
| Top Hole                   | 11 mm                |
| Stainless                  | Yes                  |
| Dyn. Load Capacity (4km/)  | 350 kg               |
| Color Tread                | White                |
| Material Type              | RoHS (EU) - Approved |
| Offset                     | 57 mm                |
| Material Thickness Bracket | 2.5 mm               |
| Materialthicknessplate     | 2.5 mm               |
| Product Weight             | 1.38 kg              |
| Temperature Range          | -20°C to +70°C       |

Numeric values in the technical specification can be nominal/rounded to the nearest standard dimension. To see exact values, please use the drawing.