

PRODUCT DATA SHEET

2024-04-09



Article number:

5L25690232V-G

Swivel castor 250 mm, PA6G-wheel

Swivel bracket. Welded, zinc plated castor and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel made of white Nylon/PA6G. Doubla Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	250 mm
Totalt height	314 mm
Load Capacity (dynamic)	3000 kg
Castor model	Swivel
Fitting	Top plate
Material Tread	Nylon PA6G (Cast)
Bearing	Double Ball bearing
Plate Size	175x140 mm
CC Distance	140x105 mm
Thread hardness (Shore°)	85° Shore D
Width of tread	80 mm
Material Hub	Nylon PA6G (Cast)
Top Hole	14 mm
Dyn. Load Capacity (4km/)	3000 kg
Color Tread	White
Material Type	RoHS (EU) - Approved
Offset	80 mm
Material Thickness Bracket	10 mm
Materialthickplate	11.5 mm
Product Weight	14.53 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.