

PRODUCT DATA SHEET

2024-04-16



Article number:

5J15680432PZ-FE

Swivel castor 150 mm, elastic PU-tyre

Swivel bracket. Welded, zinc plated castor and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel with green elastic PU-tyre. Hub made of cast iron. Double Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	150 mm
Total height	200 mm
Load Capacity (dynamic)	450 kg
Castor model	Swivel
Fitting	Top plate
Material Tread	Elastic Polyurethan
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	83° Shore A
Width of tread	38 mm
Material Hub	Cast Iron
Top Hole	11 mm
Dyn. Load Capacity (4km/)	450 kg
Color Tread	Green
Material Type	RoHS (EU) - Approved
Offset	54 mm
Material Thickness Bracket	6 mm
Material thickness plate	8 mm
Product Weight	5,38 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification can be nominal/rounded to the nearest standard dimension. To see exact values, please use the drawing.