

# PRODUCT DATA SHEET

2024-04-09



Article number:

5J15685432OZ-FE-M 

Braked castor 150 mm, total stop brake, PU-tyre

Swivel bracket. Welded, zinc plated castor fitted with a total stop brake and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel with red PU-tyre. Hub made of cast iron. Double Ball bearing.



Image may differ from the actual product.\*

## SPECIFICATIONS

Diameter	150 mm
Totalt height	200 mm
Load Capacity (dynamic)	750 kg
Castor model	Brake
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	93° Shore A
Brake	Total brake
Width of tread	50 mm
Material Hub	Cast Iron
Top Hole	11 mm
ESD	No
Stainless	No
Wheels	No
Heat Resistant	No
Fixed	No
Dyn. Load Capacity (4km/)	750 kg
Color Tread	Red
Material Type	RoHS (EU) - Approved
Offset	54 mm
Material Thickness Bracket	6 mm
Materialthickplate	8 mm
Product Weight	6.35 kg
Temperature Range	-20°C to +85°C

Numeric values in the technical specification can be nominal/rounded to the chreases standard dimension. To see exact values, please use the drawing.