

PRODUCT DATA SHEET

2024-04-10



Article number:

5J20680432OZ-FE-M 

Swivel castor 200 mm, PU-tyre

Swivel bracket. Welded, zinc plated castor and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel with red PU-tyre. Hub made of cast iron. Double Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	200 mm
Totalt height	245 mm
Load Capacity (dynamic)	1000 kg
Castor model	Swivel
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	93° Shore A
Width of tread	50 mm
Material Hub	Cast Iron
Top Hole	11 mm
ESD	No
Stainless	No
Wheels	No
Heat Resistant	No
Fixed	No
Dyn. Load Capacity (4km/)	1000 kg
Color Tread	Red
Material Type	RoHS (EU) - Approved
Offset	56 mm
Material Thickness Bracket	6 mm
Materialthickplate	8 mm
Product Weight	7.12 kg
Temperature Range	-20°C to +85°C

Numeric values in the technical specification can be nominal/rounded to the nearest standard dimension. To see exact values, please use the drawing.