

# PRODUCT DATA SHEET

2024-04-10



Article number:

5J15680432BV-HD

Swivel castor 150 mm, TPU-tyre

Swivel bracket. Welded, zinc plated castor and ball race swivel with thrust ball bearing combined alongside tapered roller bearing. Sealed and equipped with a grease nipple. Top plate fitting. Wheel axle with nut. Wheel with red TPU-tyre. Hub made of Nylon/PA6. Double Ball bearing.



Image may differ from the actual product.\*

## SPECIFICATIONS

Diameter	150 mm
Totalt height	200 mm
Load Capacity (dynamic)	600 kg
Castor model	Swivel
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Double Ball bearing
Plate Size	140x110 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	98° Shore A
Width of tread	45 mm
Material Hub	Nylon PA6
Top Hole	11 mm
Dyn. Load Capacity (4km/)	600 kg
Color Tread	Red
Material Type	RoHS (EU) - Approved
Offset	54 mm
Material Thickness Bracket	6 mm
Materialthicknessplate	8 mm
Product Weight	3,82 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification can be nominal/rounded to the nearest standard dimension. To see exact values, please use the drawing.