

PRODUCT DATA SHEET

2024-04-10



Article number:

5T15680432BV-V2

Fixed castor twin wheel 150 mm, TPU-tyre

Fixed bracket made of zinc-chromatized welded steel for twin wheel. Top plate fitting. Wheel axle with nut. Wheel with red PU-tyre. Hub made of Nylon/PA6. Double Ball bearing.



Image may differ from the actual product.*

SPECIFICATIONS

Diameter	150 mm
Totalt height	200 mm
Load Capacity (dynamic)	1100 kg
Castor model	Fix
Fitting	Top plate
Material Tread	Polyurethane
Bearing	Double Ball bearing
Plate Size	175x150 mm
CC Distance	105x80 mm
Thread hardness (Shore°)	98° Shore A
Width of tread	45 mm
Material Hub	Nylon PA6
Top Hole	12 mm
ESD	No
Stainless	No
Wheels	No
Heat Resistant	No
Fixed	Yes
Dyn. Load Capacity (4km/)	1100 kg
Color Tread	Red
Material Type	RoHS (EU) - Approved
Material Thickness Bracket	8 mm
Materialthickplate	15 mm
Product Weight	4.28 kg
Temperature Range	-20°C to +70°C

Numeric values in the technical specification can be nominal/rounded to the chreares standard dimension. To see exact values, please use the drawing.