

# PRODUCT DATA SHEET

2024-04-09



Article number:

8010005332GGG

Braked castor 100 mm, total stop brake, TPE-tyre

Swivel bracket with total stop brake. Injection moulded plastic bracket in grey PA6-GF35 with ball bearings in the swivel head. Center hole fitting. Wheel axle with nut. Wheel with grey TPE-tyre. Hub made of grey PP with threadguards. Ball bearing.



Image may differ from the actual product.\*

## SPECIFICATIONS

Diameter	100 mm
Totalt height	140 mm
Load Capacity (dynamic)	100 kg
Castor model	Brake
Fitting	Centre hole
Material Tread	TPE
Bearing	Ball bearing
Thread hardness (Shore°)	85° Shore A
Centre Bolt Hole	10.2 mm
Brake	Total brake
Width of tread	32 mm
Material Hub	Polypropylen (pp)
Wheel Pattern	EN 12530
Color Tread	Gray RAL 7012
Teststandard	EN 12530
Offset	45 mm
Ball bearing	6202-ZZ
Swivel radius	95 mm
Product Weight	0,42 kg
Temperature Range	-20°C to +50°C

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.