

# PRODUCT DATA SHEET

2024-03-13



Article number:

1605082401SSS

Braked castor 50 mm, wheel brake, TPU-tyre

Injection moulded housing in black PA6, riveted wheel axle. Wheel brake. Wheel with plain bearing and black PUR-tyre. Hub in black PP.



Image may differ from the actual product.\*

## SPECIFICATIONS

|                          |                      |
|--------------------------|----------------------|
| Diameter                 | 50 mm                |
| Totalt height            | 59 mm                |
| Load Capacity (dynamic)  | 40 kg                |
| Castor model             | Brake                |
| Fitting                  | Top plate            |
| Material Tread           | Polyurethane         |
| Bearing                  | Rivet                |
| Thread hardness (Shore°) | 98° Shore A          |
| Brake                    | Wheel brake          |
| Width of tread           | 18 mm                |
| Material Hub             | Polypropylen (pp)    |
| Color Tread              | Black                |
| Material Type            | RoHS (EU) - Approved |
| Offset                   | 27 mm                |
| Hole diameter            | 8 mm                 |
| Swivel radius            | 52 mm                |
| Product Weight           | 0,06 kg              |
| Temperature Range        | -20°C to +50°C       |

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.