

PRODUCT DATA SHEET

2024-04-09



Article number:

5A20005322SR-LG

Braked castor 200 mm, total stop brake, pneumatic-wheel

Swivel bracket with total stop brake. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Center hole fitting for M12 screw. Wheel axle with nut. Wheel with balck pneumatic rubber-tyre. Hub made of red PP. Roller bearing.



Image may differ from the actual product.*

SPECIFICATIONS

| | |
|----------------------------|----------------------|
| Diameter | 200 mm |
| Totalt height | 240 mm |
| Load Capacity (dynamic) | 60 kg |
| Castor model | Brake |
| Fitting | Centre hole |
| Material Tread | Pneumatic |
| Bearing | Roller bearing |
| Thread hardness (Shore°) | 65° Shore A |
| Centre Bolt Hole | 13 mm |
| Brake | Total brake |
| Width of tread | 50 mm |
| Hub Hole Diameter | 12 mm |
| Material Hub | Polypropylen (pp) |
| Pneumatic Wheel | Yes |
| Diameter second/outer | 24 mm |
| No. of Plies | 2 st |
| Fork Width | 61 mm |
| Color Tread | Red |
| Material Type | RoHS (EU) - Approved |
| Offset | 53 mm |
| Material Thickness Bracket | 3 mm |
| Swivel radius | 162 mm |
| Product Weight | 2,15 kg |
| Temperature Range | -20°C to +60°C |

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.