

PRODUCT DATA SHEET

2024-04-10



Article number:

5A26690332SR-LG6


Swivel castor 260 mm, pneumatic-tyre

Swivel bracket. Made of zinc-chromatized pressed sheet metal with double ball race swivel. Top plate fitting. Wheel axle with nut. Wheel with black pneumatic rubber-tyre. Hub made of red steel plate. Double Ball bearing.



Image may differ from the actual product.*

DIMENSIONS



SPECIFICATIONS

Diameter	260 mm
Totalt height	295 mm
Load Capacity (dynamic)	250 kg
Castor model	Swivel
Fitting	Top plate
Material Tread	Pneumatic
Bearing	Double Ball bearing
Plate Size	175x175 mm
CC Distance	140x140 mm
Thread hardness (Shore°)	65° Shore A
Width of tread	85 mm
Material Hub	Steel plate
Top Hole	14 mm
Pneumatic Wheel	Yes
Diameter second/outer	22 mm
No. of Plies	6 st
Dyn. Load Capacity (4km/)	250 kg
Color Tread	Black
Material Type	RoHS (EU) - Approved
Offset	55 mm
Max Air Pressure (BAR)	3.5
Material Thickness Bracket	4 mm
Materialthickplate	4 mm
Product Weight	4,81 kg

Numeric values in the technical specification can be nominal/rounded to the cneares standard dimension. To see exact values, please use the drawing.