

Broj artikla:

CONT 125 ELA K-L PL105X85+RIKT



Slika može odstupati od stvarnog proizvoda.*

Technical drawing of a circular component, likely a flange or base plate, showing dimensions in millimeters. The overall diameter is 105 mm. The central circular feature has a diameter of 82.6 mm. The distance from the center to the outer edge of the central feature is 80 mm. The distance from the center to the outer edge of the base plate is 77.4 mm. The base plate has a thickness of 62.6 mm. The central feature has a thickness of 57.4 mm. The base plate has a thickness of 60 mm. The base plate has four mounting holes, each with a diameter of 6 mm. The distance between the centers of opposite mounting holes is 85 mm.

Prečnik	125 mm
Visina gradnje	157 mm
Otpornost Na Teret	225 kg
Montaža Točka	Ploča
Tip Materijala Staze	Elastična guma
Ležaj	Kuglični ležaj
Veličina Ploče	105x85 mm
Razmak Između Centara	80x60 mm
Tvrdoća Staze (Shore°)	75° Shore A
Kočnica	Blokada usmerivača
Širina Staze	36 mm
Tip Materijala Glave Točka	Najlon PA6
Prečnik Otvora na Ploči	12,5x9 mm
Boja Gazne Površine	Siva
TestStandard	EN 12532
Pomak	42 mm
Debljina Materijala Nosača	2.5 mm
Debljina Materijala Ploče	3 mm
Poluprečnik Okretanja	129 mm
ProductWeight	1.27 kg
Temperaturni Opseg	-30°C to +70°C

Numeričke vrednosti u tehničkoj specifikaciji mogu biti nominalne/zaokružene na najbližu standardnu dimenziju. Za tačne vrednosti, koristite crtež.